


MAXI**CHARGER** ACULTRA

19.2kW*2



MAXI**CHARGER** ACULTRA

The Fastest AC Charger for Two Vehicles



FAST AND EFFICIENT

CREATE AN EXCEPTIONAL CHARGING EXPERIENCE

- At 19.2kW per port this charger leads the industry by fast charging 2 vehicles simultaneously, and generates 75 miles of range within 60 min
- Designed with ISO 15118 Plug & Charge, for a hassle-free charging experience



BEST-VALUE DESIGN

TAILORED FOR COMMERCIAL DEPLOYMENT

- Rugged design allows it to be wall-mounted or floor-mounted to support your application needs
- One-piece construction makes it easy to install resulting in lower costs and a faster ROI












SMART CHARGING

FUTURE-PROOF, FLEXIBLE AND IMPROVES YOUR BOTTOM-LINE

- Smart functionality with OCPP 1.6 and 2.0.1 compliant, can adapt its power usage and provide optimal charging today and into the future
- Reduce capital investment in power capacity

THE BIG VALUE BEHIND THE MAXI**CHARGER** ACULTRA

-  Cable Management
-  One-piece Pedestal Housing Combination
-  WiFi Hotspot Sharing
-  Power Sharing
-  8-inch HD Advertising Screen
-  APP, RFID Card, Credit Card, Mobile Payment
-  One-Stop Cloud Network Management
-  OCPP1.6 / 2.0.1
-  Weather Resistant



TECHNICAL SPECIFICATIONS

PRODUCT INFORMATION

Input/output power rating and current

2*19.2kW (240V AC*80A)

Input/output voltage

Output amperage adjustable via mobile app, from 6A to 80A
208V±15%; 240V±15%, 60Hz

Input wiring

L1/L2/PE

Input cord

Hardwired

Connector type

SAE J1772, 7.5m (25') or 5m

Ground fault detection

20mA CCID

Protection

Overcurrent, overvoltage, undervoltage, integrated surge protection

Card reader

Optional: ISO 15693, ISO 14443, NFC

Power measurement accuracy

+/- 1.0% from 1% to full scale

GENERAL CHARACTERISTICS

Enclosure rating

NEMA 3R

Operating altitude

2000m

Operating temperature range

- 40°C ~ + 50°C

Storage temperature range

- 40°C ~ + 85°C

Mounting

Wall or floor using a pedestal

Dimensions (H*W*D)

625 × 320 × 170mm

USER INTERFACE

Status indication

LED / APP / LCD (8 inch,1280*720 touch screen)

User interface

Autel Charge APP; Autel Charge Cloud

Connectivity

Bluetooth, Wi-Fi, Ethernet, 4G, RS485

Communication protocols

OCPP 1.6J (Can be upgraded to OCPP 2.0.1 later)

User authentication

APP, RFID card, Credit Cards (Optional)

SOFTWARE UPDATE

OTA updates via web portal

CERTIFICATION AND STANDARDS

Safety and compliance

UL 2231-1, UL 2231-2, UL2594, NEC Article 625, CSA C22.2, UL 916

EMC compliance

FCC 15 Class B

Certification

Energy Star, OpenADR 2.0b

Warranty

36 months, warranty extension possible
